

# AgriMetal

INC.



## SELF-PROPELLED GREENS ROLLER MODEL GR-400

14 HP KOHLER ENGINE

OPERATOR'S MANUAL



**AGRIMETAL INC.  
SELF-PROPELLED GREENS ROLLER**

**WARRANTY**

AgriMetal Incorporated (AgriMetal) warrants the new Greens Roller to be free from defects in material, under normal use and service. Obligation under this warranty shall extend for a period of 1 year (12 months) following the date of delivery to the original purchaser and shall be limited to, at the option of AgriMetal, replacement or repair of any parts found, upon inspection by AgriMetal, to be defective.

**WARRANTY CLAIMS**

The purchaser claiming under this warranty shall submit a warranty claim in the prescribed form to AgriMetal or an Authorized Dealer, for inspection by an authorized company representative.

**LIMITATIONS OF LIABILITY**

This warranty is expressly in lieu of all other warranties expressed or implied and all other obligations or liabilities on our part of any kind or character, including liabilities for alleged representations or negligence. We neither assume nor authorize any other person to assume on our behalf, any liability in connection with the subsequent sale of the Greens Roller.

This warranty shall not apply to any Greens Roller which has been altered outside the factory in any way so as, in the judgement of AgriMetal, to affect its operation or reliability, or which has been subject to misuse, neglect or accident.

This warranty does not cover parts and accessories which are under separate guarantees from the manufacturers and where service can be obtained from their service facilities. No warranty is extended to regular service items such as lubricants, belts, tires, paint and the like.

**OPERATOR'S MANUAL**

The Purchaser acknowledges having received training in the safe operation of the Greens Roller and further acknowledges that AgriMetal does not assume any liability resulting from the operation of the Greens Roller in any manner other than described in the Operator's Manual supplied at the time of purchase.

**WARRANTY VOID IF NOT REGISTERED**

# AGRIMETAL SELF-PROPELLED GREENS ROLLER

## WARRANTY REGISTRATION FORM & INSPECTION REPORT

### WARRANTY REGISTRATION

This form must be filled out by the dealer and signed by both the dealer and the customer at the time of delivery.

Customer's Name \_\_\_\_\_ Dealer Name \_\_\_\_\_

Address \_\_\_\_\_ Address \_\_\_\_\_

City, State/Prov., Code \_\_\_\_\_ City, State/Prov., Code \_\_\_\_\_

Phone Number ( \_\_\_\_ ) \_\_\_\_\_

Greens Roller Model \_\_\_\_\_

Serial Number \_\_\_\_\_

Delivery Date \_\_\_\_\_

### DEALER INSPECTION REPORT

- \_\_\_ Hydraulic Components in Good Condition
- \_\_\_ Steering Wheel Turns Freely
- \_\_\_ Chain Tension Checked
- \_\_\_ Chain and Sprockets Aligned
- \_\_\_ Fasteners Tight
- \_\_\_ Lubricate Machine
- \_\_\_ Check Tire Pressure
- \_\_\_ Retainer Installed in Drawbar Pin
- \_\_\_ Check Fluid Levels
- \_\_\_ Retainers Installed Through Brush Frame and Guards

### SAFETY

- \_\_\_ Safety Chain on Trailer Hitch
- \_\_\_ All Decals Installed
- \_\_\_ Guards and Shields Installed and Secured
- \_\_\_ Review Operating and Safety Instructions

I have thoroughly instructed the buyer on the above described equipment which review included the Operator's Manual content, equipment care, adjustments, safe operation and applicable warranty policy.

Date \_\_\_\_\_

Dealer's Rep. Signature \_\_\_\_\_

Signature \_\_\_\_\_

The above equipment and Operator's Manual have been received by me and I have been thoroughly instructed as to care, adjustments, safe operation and applicable warranty policy.

Date \_\_\_\_\_

Owner's Signature \_\_\_\_\_

|                |        |          |
|----------------|--------|----------|
| WHITE          | YELLOW | PINK     |
| AGRIMETAL INC. | DEALER | CUSTOMER |

# SERIAL NUMBER LOCATION

Always give your dealer the serial number of your AgriMetal Self-Propelled Greens Roller when ordering parts or requesting service or other information.

The serial number plate is located where indicated. Please mark the number in the space provided for easy reference.



**Model Number** \_\_\_\_\_

**Serial Number** \_\_\_\_\_

GR-400 Noise Level Chart

| Engine Speed | Reading Location     | Noise Level (dBA) |
|--------------|----------------------|-------------------|
| Low Idle     | Right Side of Driver | 62                |
|              | Left Side of Driver  | 55                |
|              | Ear                  | 70                |
| Max RPM      | Right Side of Driver | 71                |
|              | Left Side of Driver  | 70                |
|              | Ear                  | 87                |

- Radio Shack Realistic sound level meter used for test.
- All readings taken on compacted gravel surface.
- 55 dBA ambient noise level.
- Side measurements at 16 m from machine.

# TABLE OF CONTENTS

| SECTION  | DESCRIPTION   | PAGE      |
|----------|---|-----------|
| <b>1</b> | <b>Introduction .....</b>                             | <b>1</b>  |
| <b>2</b> | <b>Safety .....</b>                                   | <b>3</b>  |
| 2.1      | General Safety .....                                  | 4         |
| 2.2      | Equipment Safety Guidelines .....                     | 5         |
| 2.3      | Safety Training .....                                 | 6         |
| 2.4      | Safety Signs .....                                    | 6         |
| 2.5      | Preparation .....                                     | 7         |
| 2.6      | Maintenance Safety .....                              | 7         |
| 2.7      | Operating Safety .....                                | 8         |
| 2.8      | Transport Safety .....                                | 9         |
| 2.9      | Storage Safety .....                                  | 9         |
| 2.10     | Refuelling Safety .....                               | 9         |
| 2.11     | Tire Safety .....                                     | 9         |
| 2.12     | Gas Motor Safety .....                                | 10        |
| 2.13     | Sign-Off Form .....                                   | 11        |
| <b>3</b> | <b>Safety Sign Locations .....</b>                    | <b>13</b> |
| <b>4</b> | <b>Assembling .....</b>                               | <b>15</b> |
| 4.1      | Machine Assembly .....                                | 15        |
| <b>5</b> | <b>Operation.....</b>                                 | <b>29</b> |
| 5.1      | To the New Operator or Owner .....                    | 29        |
| 5.2      | Machine Components.....                               | 30        |
| 5.3      | Break-In .....  | 31        |
| 5.4      | Pre-Operation Checklist .....                         | 31        |
| 5.5      | Controls .....  | 32        |
| 5.6      | Attaching/Unhooking .....                             | 34        |
| 5.7      | Loading Greens Roller onto Trailer .....              | 35        |
| 5.8      | Field Operation .....                                 | 36        |
| 5.9      | Transporting .....                                    | 44        |
| 5.10     | Storage .....   | 45        |
| <b>6</b> | <b>Service and Maintenance.....</b>                   | <b>47</b> |
| 6.1      | Service.....  | 47        |
| 6.1.1    | Fluids and Lubricants .....                           | 47        |
| 6.1.2    | Greasing.....   | 47        |
| 6.1.3    | Servicing Intervals.....                              | 48        |
| 6.1.4    | Service Record.....                                   | 53        |
| 6.2      | Maintenance .....                                     | 54        |
| 6.2.1    | Cleaning Air Cleaner .....                            | 54        |
| 6.2.2    | Changing Engine Oil .....                             | 55        |
| 6.2.3    | Changing Hydraulic Oil and Filter.....                | 56        |
| 6.2.4    | Steering System Centering .....                       | 57        |
| 6.2.5    | Rolling System Chain Drive Tension and Alignment..... | 58        |
| <b>7</b> | <b>Trouble Shooting.....</b>                          | <b>59</b> |
| <b>8</b> | <b>Specifications .....</b>                           | <b>61</b> |
| 8.1      | Mechanical .....                                      | 61        |
| 8.2      | Hydraulic Fitting Torque .....                        | 62        |
| 8.3      | Bolt Torque .....                                     | 63        |
| <b>9</b> | <b>Index .....</b>                                    | <b>65</b> |

# 1 INTRODUCTION

Congratulations on your choice of an AgriMetal Model GR-400 Self-Propelled Greens Roller to complement your operation. This equipment has been designed and manufactured to meet the needs of a discerning turf care industry.

Safe, efficient and trouble free operation of your AgriMetal Greens Roller requires that you and anyone else who will be operating or maintaining the machine, read and understand the Safety, Operation, Maintenance and Trouble Shooting information contained within the Operator's Manual.



This manual covers the AgriMetal Model GR-400 Self-Propelled Greens Roller. Use the Table of Contents or Index as a guide to locate required information.

Keep this manual handy for frequent reference and to pass on to new operators or owners. Call your AgriMetal Dealer or the factory if you need assistance, information or additional copies of the manuals.

**OPERATOR ORIENTATION** - The directions left, right, front and rear, as mentioned throughout this manual, are as seen from the driver's seat and facing forward.



## 2 SAFETY

### SAFETY ALERT SYMBOL

This Safety Alert symbol means **ATTENTION! BECOME ALERT! YOUR SAFETY IS INVOLVED!**



The Safety Alert symbol identifies important safety messages on the AgriMetal Self-Propelled Greens Roller and in the manual. When you see this symbol, be alert to the possibility of personal injury or death. Follow the instructions in the safety message.

Why is SAFETY important to you?

#### 3 Big Reasons

**Accidents Disable and Kill**  
**Accidents Cost**  
**Accidents Can Be Avoided**

#### SIGNAL WORDS:

Note the use of the signal words **DANGER**, **WARNING** and **CAUTION** with the safety messages. The appropriate signal word for each message has been selected using the following guide-lines:

**SI NO LEE INGLÉS, PIDA AYUDA A ALGUIEN QUE SI LO LEA PARA QUE LE TRADUZCA LAS MEDIDAS DE SEGURIDAD.**

**DANGER** - Indicates an imminently hazardous situation that, if not avoided, will result in death or serious injury. This signal word is to be limited to the most extreme situations typically for machine components which, for functional purposes, cannot be guarded.

**WARNING** - Indicates a potentially hazardous situation that, if not avoided, could result in death or serious injury, and includes hazards that are exposed when guards are removed. It may also be used to alert against unsafe practices.

**CAUTION** - Indicates a potentially hazardous situation that, if not avoided, may result in minor or moderate injury. It may also be used to alert against unsafe practices.

If you have any questions not answered in this manual or require additional copies or the manual is damaged, please contact your dealer at AgriMetal Inc., 1006 Rue Principale, Wickham, Quebec, Canada, J0C 1S0. Phone (819) 398-6883 or fax (819) 398-5311.

# SAFETY

**YOU** are responsible for the SAFE operation and maintenance of your AgriMetal Self-Propelled Greens Roller. **YOU** must ensure that you and anyone else who is going to operate, maintain or work around the Greens Roller be familiar with the operating and maintenance procedures and related **SAFETY** information contained in this manual. This manual will take you step-by-step through your working day and alerts you to all good safety practices that should be adhered to while operating the Greens Roller.

Remember, **YOU** are the key to safety. Good safety practices not only protect you but also the people around you. Make these practices a working part of your safety program. Be certain that **EVERYONE** operating this equipment is familiar with the recommended operating and maintenance procedures and follows all the safety precautions. Most accidents can be prevented. Do not risk injury or death by ignoring good safety practices.

- Greens Roller owners must give operating instructions to operators or employees before allowing them to operate the machine, and at least annually thereafter.
- The most important safety device on this equipment is a SAFE operator. It is the operator's responsibility to read and understand ALL Safety and Operating instructions in the manual and to follow these. Most accidents can be avoided.
- A person who has not read and understood all operating and safety instructions is not qualified to operate the machine. An untrained operator exposes himself and bystanders to possible serious injury or death.
- Do not modify the equipment in any way. Unauthorized modification may impair the function and/or safety and could affect the life of the equipment.
- Think SAFETY! Work SAFELY!

## 2.1 GENERAL SAFETY


1. Read and understand the Operator's Manual and all safety signs before operating, maintaining, adjusting or unplugging the Greens Roller.



2. Have a first-aid kit available for use should the need arise and know how to use it.



3. Have a fire extinguisher available for use should the need arise and know how to use it.



4. Do not allow riders.


5. Wear appropriate protective gear. This list includes but is not limited to:

- A hard hat
- Protective shoes with slip resistant soles
- Protective glasses or goggles
- Heavy gloves
- Wet weather gear
- Hearing protection
- Respirator or filter mask



6. Install and secure all guards before starting.

7. Wear suitable ear protection for prolonged exposure to excessive noise.



8. Slow engine to low idle, stop engine, remove ignition key and wait for all moving parts to stop before servicing, adjusting, repairing or unplugging.

9. Clear the area of people, especially small children, before starting the unit.


10. Review safety related items annually with all personnel who will operating or maintaining the Greens Roller.

## 2.2 EQUIPMENT SAFETY GUIDELINES

1. Safety of the operator and bystanders is one of the main concerns in designing and developing a machine. However, every year many accidents occur which could have been avoided by a few seconds of thought and a more careful approach to handling equipment. You, the operator, can avoid many accidents by observing the following precautions in this section. To avoid personal injury or death, study the following precautions and insist those working with you, or for you, follow them.
2. In order to provide a better view, certain photographs or illustrations in this manual may show an assembly with a safety shield removed. However, equipment should never be operated in this condition. Keep all shields in place. If shield removal becomes necessary for repairs, replace the shield prior to use.
3. Replace any safety sign or instruction sign that is not readable or is missing. Location of such safety signs is indicated in this manual.
4. Never use alcoholic beverages or drugs which can hinder alertness or coordination while operating this equipment. Consult your doctor about operating this machine while taking prescription medications.
5. **Under no circumstances should young children be allowed to work with this equipment. Do not allow persons to operate or assemble this unit until they have read this manual and have developed a thorough understanding of the safety precautions and of how it works.** Review the safety instructions with all users annually.
6. This equipment is dangerous to children and persons unfamiliar with its operation. The operator should be a responsible, properly trained and physically able person familiar with machinery and trained in this equipment's operations. If the elderly are assisting with work, their physical limitations need to be recognized and accommodated.
7. Never exceed the limits of a piece of machinery. If its ability to do a job, or to do so safely, is in question - **DON'T TRY IT.**
8. Do not modify the equipment in any way. Unauthorized modification result in serious injury or death and may impair the function and life of the equipment.
9. In addition to the design and configuration of this implement, including Safety Signs and Safety Equipment, hazard control and accident prevention are dependent upon the awareness, concern, prudence, and proper training of personnel involved in the operation, transport, maintenance, and storage of the machine. Refer also to Safety Messages and operation instruction in each of the appropriate sections of the tow vehicle and machine Manuals. Pay close attention to the Safety Signs affixed to the tow vehicle and the machine.

## 2.3 SAFETY TRAINING

1. Safety is a primary concern in the design and manufacture of our products. Unfortunately, our efforts to provide safe equipment can be wiped out by a single careless act of an operator or bystander.
2. In addition to the design and configuration of equipment, hazard control and accident prevention are dependent upon the awareness, concern, prudence and proper training of personnel involved in the operation, transport, maintenance and storage of this equipment.
3. It has been said, "The best safety feature is an informed, careful operator." We ask you to be that kind of an operator. It is the operator's responsibility to read and understand ALL Safety and Operating instructions in the manual and to follow these. Accidents can be avoided.
4. **Working with unfamiliar equipment can lead to careless injuries. Read this manual, and the manual for your tractor, before assembly or operating, to acquaint yourself with the machines. If this machine is used by any person other than yourself, or is loaned or rented, it is the machine owner's responsibility to make certain that the operator, prior to operating:**
  - a. **Reads and understands the operator's manuals.**
  - b. **Is instructed in safe and proper use.**
5. Know your controls and how to stop engine and machine quickly in an emergency. Read this manual and the one provided with your tow vehicle.
6. Train all new personnel and review instructions frequently with existing workers. Be certain only a properly trained and physically able person will operate the machinery. A person who has not read and understood all operating and safety instructions is not qualified to operate the machine. An untrained operator exposes himself and bystanders to possible serious injury or death. If the elderly are assisting with work, their physical limitations need to be recognized and accommodated.



## 2.4 SAFETY SIGNS

1. Keep safety signs clean and legible at all times.
2. Replace safety signs that are missing or have become illegible.
3. Replaced parts that displayed a safety sign should also display the current sign.
4. Safety signs are available from your authorized Distributor or Dealer Parts Department or the factory.

### How to Install Safety Signs:

- Be sure that the installation area is clean and dry.
- Be sure temperature is above 50°F (10°C).
- Determine exact position before you remove the backing paper.
- Remove the smallest portion of the split backing paper.
- Align the sign over the specified area and carefully press the small portion with the exposed sticky backing in place.
- Slowly peel back the remaining paper and carefully smooth the remaining portion of the sign in place.
- Small air pockets can be pierced with a pin and smoothed out using the piece of sign backing paper.

## 2.5 PREPARATION

1. Never operate the tractor and machine until you have read and completely understand this manual, the tow vehicle Operator's Manual, and each of the Safety Messages found on the safety signs on the tow vehicle and machine.

2. Personal protection equipment including hard hat, safety glasses, safety shoes, and gloves are recommended during assembly, installation, operation, adjustment, maintaining, repairing, removal, or moving the implement. Do not allow long hair, loose fitting clothing or jewelry to be around equipment.



### 3. PROLONGED EXPOSURE TO LOUD NOISE MAY CAUSE PERMANENT HEARING LOSS!

Tractors with or without equipment attached can often be noisy enough to cause permanent, partial hearing loss. We recommend that you wear hearing protection on a full-time basis if the noise in the Operator's position exceeds 80db. Noise over 85db on a long-term basis can cause severe hearing loss. Noise over 90db adjacent to the Operator over a long-term basis may cause permanent, total hearing loss. **NOTE:** Hearing loss from loud noise (from tractors, chain saws, radios, and other such sources close to the ear) is cumulative over a lifetime without hope of natural recovery.



4. Clear working area of stones, branches or hidden obstacles that might be hooked or snagged, causing injury or damage.
5. Operate only in daylight or good artificial light.
6. Be sure machine is properly mounted, adjusted and in good operating condition.
7. Ensure that all safety shielding and safety signs are properly installed and in good condition.

## 2.6 MAINTENANCE SAFETY

1. Good maintenance is your responsibility. Poor maintenance is an invitation to trouble.

2. Follow good shop practices.

- Keep service area clean and dry.
- Be sure electrical outlets and tools are properly grounded.
- Use adequate light for the job at hand.



3. Make sure there is plenty of ventilation. Never operate the engine of the towing vehicle in a closed building. The exhaust fumes may cause asphyxiation.


4. Before working on this machine, shut off the engine, set the brake, and turn fuel valve off.

5. Never work under equipment unless it is blocked securely.

6. Always use personal protection devices such as eye, hand and hearing protectors, when performing any service or maintenance work. Use heavy gloves when handling sharp components.

7. Where replacement parts are necessary for periodic maintenance and servicing, genuine factory replacement parts must be used to restore your equipment to original specifications. The manufacturer will not be responsible for injuries or damages caused by use of unapproved parts and/or accessories.

8. A fire extinguisher and first aid kit should be kept readily accessible while performing maintenance on this equipment.



9. Periodically tighten all bolts, nuts and screws and check that all cotter pins are properly installed to ensure unit is in a safe condition.

10. When completing a maintenance or service function, make sure all safety shields and devices are installed before placing unit in service.

## 2.7 OPERATING SAFETY

1. Please remember it is important that you read and heed the safety signs on the Self-Propelled Greens Roller. Clean or replace all safety signs if they cannot be clearly read and understood. They are there for your safety, as well as the safety of others. The safe use of this machine is strictly up to you the operator.
2. All things with moving parts are potentially hazardous. There is no substitute for a cautious, safe-minded operator who recognizes potential hazards and follows reasonable safety practices. The manufacturer has designed this Greens Roller to be used with all its safety equipment properly attached, to minimize the chance of accidents. Study this manual to make sure you have all safety equipment attached.
3. If a safety shield or guard is removed for any reason, it must be replaced before the machine is again operated.
4. When the use of hand tools is required to perform any part of assembly, installation, adjustment, maintaining, repairing, removal, or moving, be sure the tools used are designed and recommended by the tool manufacturer for that specific task.
5. Personal protection equipment including hearing protection, hard hat, safety glasses, safety shoes, and gloves are recommended during assembly, installation, operation, adjustment, maintaining, repairing, removal, or moving. Do not allow long hair, loose fitting clothing, or jewelry to be around moving parts.
6. Always use two people to handle heavy, unwieldy components during assembly, installation, removal or moving.
7. Never place any part of your body where it would be in danger if movement should occur during assembly, installation, operation, maintaining, repairing, removal or moving.
8. Read Operator's Manual before starting. Review safety instructions annually.
9. Stop engine, place all controls in neutral, set park brake, remove ignition key and wait for all moving parts to stop before servicing, adjusting, repairing or unplugging the machine.
10. Do not climb on the machine or place hands in any opening when the engine is running.
11. Do not smoke when refuelling.
12. Do not exceed a safe transport speed.
13. Secure access ramps before moving or transporting machine.
14. Never use alcoholic beverages or drugs which can hinder alertness or coordination while operating this equipment. Consult your doctor about operating this machine while taking prescription medications.
15. Never allow children to operate or be around this machine.
16. Clear the work area of objects which might be picked up and snagged or entangled in the machine.
16. Keep hands, feet, hair, jewelry, and clothing away from all moving and/or rotating parts.

## 2.8 TRANSPORT SAFETY

1. The machine is not designed or equipped to travel on public roads. Do not drive or transport on public roads
2. Use the trailer when moving from place to place.
3. Do not exceed 16 k/h (10 mph) when moving.
4. Plan your route to avoid rough terrain.
5. Always use a tow vehicle of less than 24 horsepower when moving the unit.
7. Use a drawbar pin with provisions for a retainer. Install the retainer. Attach safety chain between tow vehicle and machine before moving.
8. Do not drink and drive.
9. Never allow riders on either tow vehicle or machine.

## 2.9 STORAGE SAFETY

1. Store the unit in an area away from human activity.
2. Do not permit children to play on or around the stored machine.
3. Store the unit in a dry, level area. Support the hitch and wheels with planks if required.

## 2.10 REFUELLING SAFETY

1. Handle fuel with care. It is highly flammable.
2. Allow engine to cool for 5 minutes before refuelling. Clean up spilled fuel before restarting engine.
3. Do not refuel the machine while smoking or when near open flame or sparks.
4. Fill fuel tank outdoors.
5. Prevent fires by keeping machine clean of accumulated trash, grease and debris.



## 2.11 TIRE SAFETY

1. Failure to follow proper procedures when mounting a tire on a wheel or rim can produce an explosion which may result in serious injury or death.
2. Do not attempt to mount a tire unless you have the proper equipment and experience to do the job.
3. Have a qualified tire dealer or repair service perform required tire maintenance.
4. When replacing worn tires, make sure they meet the original tire specifications. Never undersize.

## 2.12 GAS MOTOR SAFETY

**BEFORE STARTING ENGINE, READ AND UNDERSTAND THE OPERATING AND MAINTENANCE INSTRUCTIONS THAT CAME WITH YOUR ENGINE.**

### **WARNING: DO NOT**

1. DO NOT run engine in an enclosed area. Exhaust gases contain carbon monoxide, an odorless and deadly poison.
2. DO NOT place hands or feet near moving or rotating parts.
3. DO NOT store, spill, or use gasoline near an open flame, or devices such as a stove, furnace, or water heater which use a pilot light or devices which can create a spark.
4. DO NOT refuel indoors where area is not well ventilated. Outdoor refuelling is preferred.
5. DO NOT fill fuel tank while engine is running. Allow engine to cool for 5 minutes before refueling. Store fuel in approved safety containers.
6. DO NOT remove fuel tank cap while engine is running.
7. DO NOT operate engine if gasoline is spilled. Move machine away from the spill and avoid creating any ignition until the gasoline has evaporated.
8. DO NOT smoke when filling fuel tank.
9. DO NOT choke carburetor to stop engine. Whenever possible, gradually reduce engine speed before stopping.
10. DO NOT run engine above rated speeds. This may result in injury.
11. DO NOT tamper with governor springs, governor links or other parts which may increase the governed engine speed.
12. DO NOT tamper with the engine speed selected by the original equipment manufacturer.
13. DO NOT check for spark with spark plug or spark plug wire removed. Use an approved tester.

14. DO NOT crank engine with spark plug removed. If engine is flooded, place throttle in "FAST" position and crank until engine starts.
15. DO NOT strike flywheel with a hard object or metal tool as this may cause flywheel to shatter in operation. Use proper tools to service engine.
16. DO NOT operate engine without a muffler. Inspect periodically and replace, if necessary. If engine is equipped with muffler deflector, inspect periodically and replace, if necessary with correct deflector.
17. DO NOT operate engine with an accumulation of grass, leaves, dirt or other combustible materials in the muffler area.
18. DO NOT use this engine on any forest covered, brush covered, or grass covered unimproved land unless a spark arrester is installed on the muffler. The arrester must be maintained in effective working order by the operator. In the State of California the above is required by law (Section 4442 of the California Public Resources Code). Other states may have similar laws. Federal laws apply on federal lands.
19. DO NOT touch hot muffler, cylinder or fins because contact may cause burns.
20. DO NOT run engine with air cleaner or air cleaner cover removed.

### **WARNING: DO**

1. ALWAYS DO remove the wire from the spark plug when servicing the engine or equipment TO PREVENT ACCIDENTAL STARTING. Disconnect the negative wire from the battery terminal if equipped with a 12 volt starting system.
2. DO keep cylinder fins and governor parts free of grass and other debris which can affect engine speed.
3. DO examine muffler periodically to be sure it is functioning effectively. A worn or leaking muffler should be repaired or replaced as necessary.
4. DO use fresh gasoline. Stale fuel can gum carburetor and cause leakage.
5. DO check fuel lines and fittings frequently for cracks or leaks. Replace if necessary.





### 3 SAFETY SIGN LOCATIONS

The types of safety signs and locations on the equipment are shown in the illustrations that follow. Good safety requires that you familiarize yourself with the various safety signs, the type of warning and the area, or particular function related to that area, that requires your SAFETY AWARENESS.

- Think SAFETY! Work SAFELY!



PN: NC13-33-0183



PN: NC13-33-0185



PN: NC13-33-0351

REMEMBER - If safety signs have been damaged, removed, become illegible or parts replaced without safety signs, new signs must be applied. New safety signs are available from your authorized dealer.

The types of safety signs and locations on the equipment are shown in the illustrations that follow. Good safety requires that you familiarize yourself with the various safety signs, the type of warning and the area, or particular function related to that area, that requires your SAFETY AWARENESS.

- Think SAFETY! Work SAFELY!



PN: NC13-33-0288



PN: NC13-33-0247

REMEMBER - If safety signs have been damaged, removed, become illegible or parts replaced without safety signs, new signs must be applied. New safety signs are available from your authorized dealer.

## 4 ASSEMBLING

### 4.1 MACHINE ASSEMBLY


The machine is shipped from the factory in a partially disassembled configuration and attached to a pallet that provides for easy moving and handling. Always use tools, equipment and forklifts of appropriate size and capacity for the job. Always use 2 men when lifting, moving and assembling the machine.

**When the machine is shipped, follow this procedure when preparing for the customer:**


1. Clear the area of bystanders especially small children before starting.
2. Remove the pallet tie-downs.
3. Use a forklift to lift the pallet/machine from the truck. Carry the load close to the ground as it is moved to the assembly area and positioned.
4. Cut and remove the straps securing the roller and trailer to the pallet.



**Strapped**



**Straps Cut**




**Straps Removed**

**Fig. 1 SHIPPING**

5. Remove hitch from pallet by removing screws securing it.



**Clevis Screw**



**Pole Screw**

**Fig. 2 HITCH**

6. Remove anchor bolts from hitch mounting channel under trailer frame.



**Bolts**

7. Remove hitch and bring to front of pallet.



**Removed**


**Fig. 3 ANCHOR BOLTS**

8. Attach hitch to trailer with anchor bolts and tighten to their specified torque.



**Fig. 4 ANCHOR BOLTS**

9. Position hitch assembly:
  - a. Install hitch.



**Hitch Installed**

- b. Turn jack to extend wheel in the down direction.
    - c. Lower wheel until it touches the ground.



**Turn Jack**

**Fig. 5 POSITION JACK**

10. Remove front frame anchor:

a. Remove anchor screws.



**Anchor Screws**

b. Remove anchor bolt.



**Anchor Bolt**

c. Remove anchor frame.



**Frame Removed**

**Fig. 6 FRAME ANCHOR**


11. Attach trailer to tow unit:

a. Align hitch and clevis.



**Aligning**

b. Install drawbar pin and retainer.



**Drawbar Pin**

c. Connect safety chain.



**Safety Chain**

d. Retract jack and rotate 90° into its stowed position.



**Jack Stowed**

**Fig. 7 HOOKING UP**

12. Drive trailer off the pallet.



**Fig. 8 DRIVING FORWARD**

13. Connect battery:

- a. Remove anchor bolts from battery pole.



**Shipping**

- b. Connect cable.




**Anchor Bolt**

- c. Tighten anchor bolt to its specified torque.



**Connecting**

- d. Move plastic shield over battery pole to cover cable connection.



**Cover**

**Fig. 9 CONNECT BATTERY**

14. Install ignition key:

a. Remove key from manual cannister.



**Manual Cannister**

b. Insert key into ignition switch.



**Ignition Switch**

**Fig. 10 IGNITION KEY**

15. Lower trailer ramp:

a. Cut plastic tie to rear support bracket.



**Rear Plastic Tie**

b. Release rear support bracket latch.



**Bracket Latch**

c. Cut plastic tie to front support bracket.



**Front Plastic Tie**

d. Release front support bracket.



**Bracket Released**

**Fig. 11 RAMP**

16. Use the handle to lower the ramp to the ground.

**NOTE**

Do not unload machine unless trailer is attached securely to tow vehicle.



**Fig. 12 RAMP LOWERED**

17. Add gas to fuel tank:
- a. Raise seat assembly.



**Seat Assembly**

- b. Remove gas cap.



**Gas Cap**

- c. Add fuel to tank.
- d. Close fuel tank cap.



**Refueling**

- e. Lower seat assembly into its operating configuration.



**Seat Assembly Lowered**



**Fig. 13 REFUELING**

18. Unload Greens Roller:

- a. Climb on seat.
- b. Start engine.

**NOTE**

Do not unload machine unless trailer is attached securely to tow vehicle.

- c. Drive machine down the ramp.

- Starting

- Down

- d. Off ramp.



**Starting Engine**



**Starting**



**Starting**



**Down Ramp**

**Fig. 14 UNLOADING**

19. Remove trailer frame shipping anchor bolt and stow.



**Fig. 15 SHIPPING ANCHOR BOLT**



## 5 OPERATION



### OPERATING SAFETY

- Read Operator's Manual before starting. Re-view safety instructions annually.
- If a safety shield or guard is removed for any reason, it must be replaced before the machine is again operated.
- When the use of hand tools is required to perform any part of assembly, installation, adjustment, maintaining, repairing, removal, or moving, be sure the tools used are designed and recommended by the tool manufacturer for that specific task.
- Always use two people to handle heavy, unwieldy components during assembly, installation, removal or moving.
- Never place any part of your body where it would be in danger if movement should occur during assembly, installation, operation, maintaining, repairing, removal or moving.
- Stop engine, place all controls in neutral, set park brake, remove ignition key and wait for all moving parts to stop before servicing, adjusting, repairing or unplugging the machine.
- Do not climb on the machine or place hands in any opening when the engine is running.
- Do not smoke when refuelling.
- Do not exceed a safe transport speed.
- Secure access ramps before moving or transporting machine.
- Never use alcoholic beverages or drugs which can hinder alertness or coordination while operating this equipment. Consult your doctor about operating this machine while taking prescription medications.
- Never allow children to operate or be around this machine.
- Clear the work area of objects which might be picked up and snagged or entangled in the machine.
- Keep hands, feet, hair, jewelry, and clothing away from all moving and/or rotating parts.

### 5.1 TO THE NEW OPERATOR OR OWNER

AgriMetal Self-Propelled Greens Rollers are designed to efficiently roll over a grass-covered surface to keep it level and trim. It works well on most grass surfaces including golf course greens.

**In addition to the design and configuration of equipment, hazard control and accident prevention are dependent upon the awareness, concern, prudence and proper training of personnel involved in the operation, transport, maintenance and storage of equipment. It is the responsibility of the owner or operator to read this manual and to train all other operators before they start working with the machine.**

**Follow all safety instructions exactly. Safety is everyone's business. By following recommended procedures, a safe working environment is provided for the operator, bystanders and the area around the worksite. Untrained operators are not qualified to operate the machine.**

Many features incorporated into this machine are the result of suggestions made by customers like you. Read this manual carefully to learn how to operate the machine safely and how to set it to provide maximum field efficiency. By following the operating instructions in conjunction with a good maintenance program, your Greens Roller will provide many years of trouble-free service.

## 5.2 MACHINE COMPONENTS

The AgriMetal Greens Roller is a self-propelled machine designed to roll over golf course greens to keep them even for consistent putting. It is powered by a small gas engine that turns a hydraulic pump that provides pressurized oil to drive the rollers. The operator sits at right angles to the direction of travel to provide good operating visibility in each direction.

Optional brushes can be mounted on each side of the frame to sweep the green while it is being rolled.

The steering wheel turns the right roller assembly to manoeuvre the machine where the operator wants to go. Foot pedals on each side of the console allow the operator to select the direction of travel.

A trailer is provided with the roller to provide a convenient way to move the machine. Lock straps on each side of the frame secure the ramps in the UP position for transporting.



Fig. 16 PRINCIPLE COMPONENTS

## 5.3 BREAK-IN

Although there are no operational restrictions on the Greens Roller when it is used for the first time, it is recommended that the following mechanical items be checked:

### A. After operating for 1 hour:

1. Check alignment of chains and sprockets. Align as required.
2. Check chain tension.
3. Torque all fasteners and hardware.
4. Check condition of drive bearings.
5. Check the rollers and rotating parts for entangled material. Remove any entangled material.
6. Check trailer tire pressure. Inflate as required.
7. Check engine fluid levels. Top up as required.

### B. After operating for 5 and 10 hours:

1. Repeat steps 1 through 7 listed above. (Section A).
2. Change engine oil.
3. Go to the normal servicing and maintenance schedule as defined in the Maintenance Section.

## 5.4 PRE-OPERATION CHECKLIST

Efficient and safe operation of the AgriMetal Self-Propelled Greens Roller requires that each operator reads and understands the operating procedures and all related safety precautions outlined in this section. A pre-operation checklist is provided for the operator. It is important for both personal safety and for maintaining the machine in good mechanical condition that this checklist be followed.

Before operating the Greens Roller and each time thereafter, the following areas should be checked off:

1. Lubricate the machine per the schedule outline in the Maintenance Section.
2. Check the tension and alignment of the roller drive chains. Align as required.
3. Check the rollers and rotating parts. Remove any twine, wire or other material that has become entangled.
4. Check that all bearings turn freely. Replace any that are rough or seized.
5. Make sure that all guards and shields are in place, secured and functioning as designed.
6. Check engine fluid levels. Top up as required.

## 5.5 CONTROLS

Before starting to work, all operators should familiarize themselves with the location and function of the controls.

### 1. Gas Engine:

A small Honda gas engine is used with the unit. Always read the engine Operator's manual supplied with the machine for the detailed operating procedures.

#### a Ignition Switch:

This key operated switch controls the electrical power to start the engine.

**OFF** - Turn the key fully counterclockwise to stop the fuel flow and turn the engine off.

**RUN** - Turn clockwise to detent on the run position. This is the position where the engine will continue to run.

**START** - Turn fully clockwise to the last spring-loaded detent position to engage the starter solenoid and start the engine. Release the key when the engine starts and it will return to the RUN position.

#### b. Fuel Shut-Off Valve:

Each engine is equipped with a valve between the fuel tank and carburetor. Slide the fuel valve toward the block to turn ON and away for OFF. Turn the fuel OFF when not in use or before transporting.

#### c. Choke:

This lever controls the position of the choke. Move the lever rearward to close the choke for starting when the engine is cold. Move the lever forward to open the choke as the engine warms. Always move the lever fully forward when operating the machine.

#### d. Throttle :

This lever, through a push-pull cable, sets the throttle position. Move the lever forward to set the engine speed at maximum RPM. Move the lever rearward to set the engine speed at low idle.




Fig. 17 ENGINE CONTROLS

#### e. Starting Rope:

This retracting rope and T bar is used to turn the engine over for starting. Grasp the T bar firmly and pull the rope sharply to start the engine.

2. **Steering Wheel:**


The steering wheel sets and controls the direction of the machine movement by turning the right roller. Turn wheel clockwise to turn to the right and counterclockwise to turn to the left. Use in conjunction with the direction of movement (below) when turning.

3. **Directional Foot Pedals:**

The machine is designed with two spring-loaded-to-neutral pedals that determine the machine's direction and speed of movement.

- a. Depress and hold the right pedal to move to the right. Depress further to increase speed to the right.
- b. Depress and hold the left pedal to move the machine to the left. Depress further to increase speed to the left.

Release the pedals and they will return to neutral and the machine will stop.



**Fig. 18 OPERATOR STATION CONTROLS**

## 5.6 ATTACHING/UNHOOKING

The Greens Roller on its trailer should always be located on a level, dry area that is free of debris and other foreign objects. When attaching the machine to a utility cart or similar tow vehicle, follow this procedure:

1. Clear the area of bystanders, especially small children.
2. Make sure there is enough room and clearance to safely back up to the machine.
3. While backing up, align the hitch with the drawbar.
4. Stop tow vehicle, remove ignition key and wait for all moving parts to stop before dismounting.
5. Use a drawbar pin with provisions for a mechanical retainer. Install the retainer.

### NOTE

If more height adjustment is needed on the hitch, unbolt clevis and turn upside down. Tighten mounting bolts to their specified torque.

6. Attach the safety chain around the drawbar cage to prevent unexpected separation.
7. Retract jack, retract anchor pin, rotate 90°, and release anchor pin to secure.

8. Reverse the above procedure when unhooking from tow vehicle.



Aligning



Pin / Retainer



Safety Chain



Jack

Fig. 19 ATTACHING

## 5.7 LOADING GREENS ROLLER ON TRAILER

The Greens Roller is designed with a trailer that allows it to be easily and conveniently moved from location to location behind a utility cart or similar tow vehicle. When loading, follow this procedure:

1. Clear the area of bystanders, especially small children.
2. Raise and pin brush frames in their UP position (if so equipped).
3. Attach trailer to tow unit.
4. Make sure there is enough room and clearance to drive up to the trailer.
5. Align the machine with the ramp.
6. Drive to the right up the ramp.
7. Align the frame of the right roller with the center of the trailer frame.

### NOTE

Do not unload machine unless trailer is attached securely to tow vehicle.

8. Drive on trailer until roller is fully on the trailer.
9. Stop engine and wait for all moving parts to stop before dismounting.

10. Raise and latch the loading ramps to the ramp support straps.

### IMPORTANT

Never tow trailer unless both ramp latches are securely engaged.

11. Ensure both ramp latches are positively engaged.
12. Reverse the above procedure when unloading.



Aligning



Climbing



On Trailer

Fig. 20 DRIVING ONTO TRAILER



Fig. 21 LATCHES ENGAGED

## 5.8 FIELD OPERATION



# OPERATING SAFETY

- Read Operator's Manual before starting. Re-view safety instructions annually.
- If a safety shield or guard is removed for any reason, it must be replaced before the machine is again operated.
- When the use of hand tools is required to perform any part of assembly, installation, adjustment, maintaining, repairing, removal, or moving, be sure the tools used are designed and recommended by the tool manufacturer for that specific task.
- Always use two people to handle heavy, unwieldy components during assembly, installation, removal or moving.
- Never place any part of your body where it would be in danger if movement should occur during assembly, installation, operation, maintaining, repairing, removal or moving.
- Stop engine, place all controls in neutral, set park brake, remove ignition key and wait for all moving parts to stop before servicing, adjusting, repairing or unplugging the machine.
- Do not climb on the machine or place hands in any opening when the engine is running.
- Do not smoke when refuelling.
- Do not exceed a safe transport speed.
- Secure access ramps before moving or transporting machine.
- Never use alcoholic beverages or drugs which can hinder alertness or coordination while operating this equipment. Consult your doctor about operating this machine while taking prescription medications.
- Never allow children to operate or be around this machine.
- Clear the work area of objects which might be picked up and snagged or entangled in the machine.
- Keep hands, feet, hair, jewelry, and clothing away from all moving and/or rotating parts.

Although the Greens Roller is easy to use, each operator should review this section to familiarize himself with the detailed safety and operating procedures. When using the machine, follow this procedure:

1. Clear the area of bystanders, especially small children.
2. Move or transport machine to working area.



Fig. 22 MOVING / TRANSPORTING

3. Release loading ramp lock and lower ramp.




**Locks**

4. Start engine.



**Start Engine**

5. Use the foot pedals to move machine.



**Foot Pedals**

6. Move the machine to the left off the rear of the trailer and off the loading ramp.



**Drive Down Ramp**

7. Drive to the green.




**Unloaded**


**Fig. 23 UNLOADING**

5. **Starting Engine:**

- a. Stand on the right side of the engine compartment.
- b. Open fuel valve.
- c. Close the choke if the engine is cold.
- d. Move the throttle to its 1/2 throttle position.
- e. Turn ignition fully clockwise to engage the starter.
- f. Gradually open the choke.
- g. Run the engine for a few minutes to allow it to warm.
- h. Increase throttle setting to maximum speed for operation.
- i. Use the foot pedals and steering wheel to move and manoeuvre machine.



**Ignition Switch**



**Foot Pedals**



**Grass**

**Fig. 24 STARTING / STOPPING**

6. **Stopping:**

- a. Slow engine to low idle.
- b. Stop engine by turning ignition switch OFF.

7. **Emergency Stopping:**

Stop forward motion and stop machine engine if an emergency occurs. Correct emergency situation before starting engine and resuming work.

8. Drive to the working area.

9. **Travel Speed:**

Set the travel speed appropriate for the job being done. Do not exceed 5 mph (8 k/h) to minimize bouncing while rolling.

10. **Travel Pattern:**

A variety of driving patterns can be used when rolling a green. However each operator is responsible to develop their own pattern appropriate for the shape of the green.



Fig. 25 WORKING

Start by rolling back and forth from side to side and turning at the edge of the green.



Fig. 26 ROLLING

11. **Turning:**

Use the steering wheel in combination with the directional pedals to pivot the right roller and turn the machine.



Right



Left


Fig. 27 TURNING

12. **Pin:**

Remove the pin from the hole when rolling to prevent any damage. Replace it after rolling the area.

**13. Cleaning:**

It is recommended that each roller head be thoroughly washed after each use to eliminate the chance of debris building up in the roller assembly. Direct the flow from a high-pressure washer through the holes on top of each deck to clean the rollers.



**Right Side**



**Left Side**

**Fig. 28 CLEANING**

**14. Brushes:**

Optional brushes are available to mount on each roller frame if required. Each brush frame is hinged to the roller assembly frame and secured with a pin. Remove pin and lower brush frame when not in use. Always raise and pin brush frame before loading machine on trailer.



**Up**



**Down**

**Fig. 29 BRUSHES**

## 15. Operating Hints:

- a. Do not allow riders.
- b. Travel at 3 to 5 mph (5 to 8 k/h) to get the best results and eliminate bouncing.

### NOTE

Better and more consistent results are obtained when driving at a slower speed when rolling.



Fig. 30 WORKING

- c. The seat can be adjusted as required for operator comfort. Release the latch below the front part of the seat and slide seat to the desired position. Release latch and seat rail will lock into position.



Back



Mid



Forward

Fig. 31 SEAT POSITION

- d. Remove the lock pin from the brush frames to lower the brushes into their working configuration. Use on the greens to spread and even any dressing material used on the green. Brush use will maintain an even and level green for the best results.

Raise and pin the brushes in their UP positions before loading on the transport vehicle.



**Up**




**Lock Pin**



**Down**

**Fig. 33 BRUSH LOCK PIN**

- e. Maintain the steering (front pedal settings) so the machine doesn't creep or move when started. Release the hydrostatic centering mechanism to allow the system to return to neutral, tighten centering system and use the pedal linkages to adjust to neutral.



**Fig. 34 STEERING SYSTEM**

## 5.9 TRANSPORTING




### TRANSPORT SAFETY

- The machine is not designed or equipped to travel on public roads. Do not drive or transport on public roads
  - Use the trailer when moving from place to place.
  - Do not exceed 16 k/h (10 mph) when moving.
  - Plan your route to avoid rough terrain.
  - Always use a tow vehicle of less than 24 horsepower when moving the unit.
  - Use a drawbar pin with provisions for a retainer.
- Install the retainer. Attach safety chain between tow vehicle and machine before moving.
- Do not drink and drive.
  - Never allow riders on either tractor or machine.
  - Never allow riders on either tow vehicle or machine.

When transporting the machine, review and follow these instructions:

1. Clear the area of bystanders, especially small children.
2. Do not drive on a public road as the machine is not equipped with the required lights and reflectors.
3. Use a trailer to move the Greens Roller from work-site to work-site.
4. Insure that the trailer is securely attached to the tow vehicle with a mechanical retainer through the drawbar pin. Always use a safety chain between the tow vehicle and trailer.
5. Do not allow riders.
6. Never exceed a safe travel speed.
7. Always move fuel valve into its OFF position before transporting machine.



Transporting



Fuel Valve

Fig. 35 TRANSPORTING

## 5.10 STORAGE



### STORAGE SAFETY

- Store the unit in an area away from human activity.
- Do not permit children to play on or around the stored machine.
- Store the unit in a dry, level area. Support the frame with planks if required.

At the end of the season, the machine should be thoroughly inspected and prepared for storage. Repair or replace any worn or damaged components to prevent any unnecessary down time at the beginning of the next season. Follow this procedure:

1. Turn fuel valve OFF.
2. Thoroughly wash the machine with a pressure washer or water hose to remove all dirt, mud, debris or residue.
3. Make sure all the water drains out of all areas of the machine.
4. Lubricate all grease points to remove any water residue from washing.
5. Remove any material that has become entangled around any moving part.
6. Touch up all paint nicks and scratches to prevent rusting.
7. Move the machine to its storage area.
8. Store in a dry, level spot.
9. Store in an enclosed building if possible.
10. Unhook trailer from the tow vehicle (see Section 5.8).
11. Place planks under the wheels and hitch for added support if required.
12. Store in an area away from human activity.
13. Do not allow children to play around the stored unit.



On Trailer



Off Trailer

Fig 36 STORED



## 6 SERVICE AND MAINTENANCE



### MAINTENANCE SAFETY

- Good maintenance is your responsibility. Poor maintenance is an invitation to trouble.
- Follow good shop practices.
  - Keep service area clean and dry.
  - Be sure electrical outlets and tools are properly grounded.
  - Use adequate light for the job at hand.
- Make sure there is plenty of ventilation. Never operate the engine of the towing vehicle in a closed building. The exhaust fumes may cause asphyxiation.
- Before working on this machine, shut off the engine, set the brake, and turn fuel valve off.
- Never work under equipment unless it is blocked securely.
- Always use personal protection devices such as eye, hand and hearing protectors, when performing any service or maintenance work. Use heavy gloves when handling sharp components.
- Where replacement parts are necessary for periodic maintenance and servicing, genuine factory replacement parts must be used to restore your equipment to original specifications. The manufacturer will not be responsible for injuries or damages caused by use of unapproved parts and/or accessories.
- A fire extinguisher and first aid kit should be kept readily accessible while performing maintenance on this equipment.
- Periodically tighten all bolts, nuts and screws and check that all cotter pins are properly installed to ensure unit is in a safe condition.
- When completing a maintenance or service function, make sure all safety shields and devices are installed before placing unit in service.

## 6.1 SERVICE

### 6.1.1 FLUIDS AND LUBRICANTS

1. **Grease:**  
Use an SAE multipurpose high temperature grease with extreme pressure (EP) performance. Also acceptable is an SAE multipurpose lithium base grease.
2. **Engine Oil:**  
Use an SAE 5W30 multi-viscosity oil meeting the American Petroleum Institute (API) classification of SF, SG, SH or SJ for normal operating temperatures. Consult the engine manual for unusual operating conditions. Do not mix oil types or viscosities.  
  
Crankcase Capacity: 1.0 L (1.0 US qt)
3. **Engine Gasoline:**  
Use a standard automotive super unleaded gasoline for all operating conditions.  
  
Fuel Tank Capacity: 1.0 US gal (3.7 liter)
4. **Hydraulic Oil:**  
Use a heavy duty motor oil (20W50, API Rating SM-SL) for all applications.  
  
Reservoir Capacity: 7.0 US gal (26.0 liter)
5. **Storing Lubricants:**  
Your machine can operate at top efficiency only if clean lubricants are used. Use clean containers to handle all lubricants. Store them in an area protected from dust, moisture and other contaminants.

### 6.1.2 GREASING

Use the Maintenance Checklist provided to keep a record of all scheduled maintenance.

1. Use a hand-held grease gun for all greasing.
2. Wipe grease fitting with a clean cloth before greasing, to avoid injecting dirt and grit.
3. Replace and repair broken fittings immediately.
4. If fittings will not take grease, remove and clean thoroughly. Also clean lubricant passageway. Replace fitting if necessary.

### IMPORTANT

Over-greasing may damage bearing seals. If seals are damaged, replace bearings immediately.

### 6.1.3 SERVICING INTERVALS

#### 8 Hours or Daily

1. Check engine oil level.



Fig. 37 DIPSTICK

2. Check engine fuel level.



Fig. 38 GAS TANK

3. Wash roller heads after each use.



Fig. 39 ROLLER HEADS


4. Clean machine.



Fig. 40 MACHINE

**40 Hours or MONTHLY**

1. Grease the roller shaft bearings with 1 shot of grease.



**Front**



**Rear**


**Fig. 41 ROLLER SHAFT BEARINGS**

2. Use a spray-on grease to lubricate roller drive chains.




**Fig. 48 ROLLER DRIVE CHAINS**

- Grease the steering cylinder end with 1 shot of grease.



**Fig 42 STEERING CYLINDER END**

- Check the oil level in the hydraulic tank.



**Fig 43 SIGHT GLASS**


- Clean engine air cleaner.



**Fig 44 AIR CLEANER**

**100 Hours or 3 Months:**

1. Change engine oil.




**Fig. 45 ENGINE**

2. Check tire pressure.



**Fig. 46 TIRE (TYPICAL)**

3. Check tension of the drive chain on each roller assembly.



**Fig. 47 CHAINS (TYPICAL)**

**Annually**

1. Change hydraulic system oil filter.



**Fig. 49 HYDRAULIC FILTER**

**Bi-Annually or Every 2 Years**

1. Change oil in hydraulic system. Use a heavy duty motor oil (20W50, API Rating SM-SL) for all applications.



**Fig. 50 HYDRAULIC SYSTEM**



## 6.2 MAINTENANCE

By following a careful service and maintenance program for your machine, you will enjoy many years of trouble-free operation.

### 6.2.1 CLEANING AIR CLEANER

1. Review the Operator's Manual for the engine.
2. Place all controls in neutral, stop engine and turn ignition off before maintaining.
3. Remove bolts anchoring engine cover to platform and raise engine cover.
4. Remove the cover over the air cleaner.
5. Remove the air cleaner from the engine.
6. Use an air hose to blow the dust and debris out of the foam.
7. Install new air cleaner.
8. Install and secure the cover.
9. Lower engine assembly cover and secure with anchor bolts.
10. Tighten anchor bolts to their specified torque.




Fig. 51 AIR CLEANER

## 6.2.2 CHANGING ENGINE OIL

1. Review the Operator's Manual for the engine.
2. Place all controls in neutral, stop engine and remove ignition key before maintaining.
3. Allow the engine to cool before changing the oil. Hot oil can cause burns if it contacts exposed skin. It is best to change oil while the engine is warm to keep the contaminants in suspension.
4. Place a pan under the drain plug.
5. Remove the drain and allow the oil to drain for 10 minutes.
6. Install and tighten the drain plug.
7. Dispose of the used oil in an approved container.
8. Fill the crankcase with specified oil.
9. Run the engine for 1-2 minutes and check for oil leaks.
10. If leaks are found around the drain plug, tighten slightly.
11. Check engine oil level. Top up as required.



**Fig. 52 ENGINE**

### 6.2.3 CHANGING HYDRAULIC OIL AND FILTER

1. Review the Operator's Manual for the engine.
2. Place all controls in neutral, stop engine, turn off ignition and wait for all moving parts to stop before changing oil and filter.
3. Allow the engine to cool before changing the oil. Hot oil can cause burns if it contacts exposed skin. It is best to change oil while the engine is warm to keep the contaminants in suspension.
4. Place a pan under the drain plug.
5. Remove the drain and allow the oil to drain for 10 minutes.
6. Install and tighten the drain plug.
7. Dispose of the used oil in an approved container.
8. Remove hydraulic oil filter.
9. Apply a light coat of oil to the O ring and install the replacement filter. Snug up by hand and then tighten another 1/2 turn.
10. Fill the hydraulic oil reservoir with specified oil.
11. Run the engine for 1 to 2 minutes and check the hydraulic system for oil leaks.
12. If leaks are found around the drain plug or filter, tighten slightly. Repeat step 11.
13. Check oil level in reservoir. Top up as required.




Fig. 53 HYDRAULIC SYSTEM

## 6.2.4 STEERING SYSTEM CENTERING

The machine steering system consists of a mechanism attached to the hydrostatic output shaft and foot pedal linkages. Each should be set so the machine doesn't move or creep when the engine is started.

To check and set steering centering, follow this procedure:

1. Clear the area of bystanders, especially small children.
2. Place all controls in neutral, stop engine, turn off ignition and wait for all moving parts to stop before servicing.
3. Loosen the mechanism attaching to the hydrostatic output shaft.
4. Tap gently to allow output shaft to move to its neutral position.
5. Tighten mechanism attaching to output shaft.
6. Adjust the foot pedal ball joint linkages to move to their neutral drive position.
7. Tighten hardware to their specified torque.
8. Start engine and check neutral setting. Re-adjust as required.



**Output Shaft Mechanism**



**Left Pedal**



**Right Pedal**


**Fig. 54 STEERING SYSTEM CENTERING**

## 6.2.5 ROLLING SYSTEM CHAIN DRIVE TENSION AND ALIGNMENT

Roller chains transmit rotational power between the hydraulic drive motor and the rollers. Spring-loaded idlers maintain the chain tension.

To check the tension of the roller drive chains, follow this procedure:

1. Clear the area of bystanders, especially small children.
2. Position machine on a level concrete surface.
3. Place all controls in neutral, stop engine, turn off ignition and wait for all moving parts to stop before servicing.
4. The chain is properly tensioned when it can move slightly.
5. Monthly apply a heavy grease to chains to prevent rusting and to lubricate. Apply sparingly to prevent grease dripping on greens.



**Fig. 55 CHAIN DRIVES**

# 7 TROUBLE SHOOTING

The AgriMetal Self-Propelled Greens Roller is designed to roll over a grass area, particularly golf greens, to level them and keep them smooth and even. It is a simple system that requires minimal maintenance.

In the following Trouble Shooting section, we have listed many of the problems, causes and solutions that can help you to solve the problems that you might encounter.

If you encounter a problem that is difficult to solve, even after having read through this trouble shooting section, please call your dealer or the factory. Before you call, please have this Operator's Manual and the serial number of your machine at hand.

| PROBLEM  | CAUSE                                  | SOLUTION                                       |
|--|--|--|
| Engine won't run.                                    | No fuel.                               | Fill fuel tank.                                |
|  |  | Open fuel line valve.                          |
| Machine doesn't move.                                | Low hydraulic oil level.               | Check oil level and top up as required.        |
|  | Plugged hydraulic oil filter.          | Change oil filter.                             |
| Machine creeps when foot pedal released.             | Neutral on hydrostatic pump has moved. | Adjust hydrostatic pump neutral position.      |
|  |  | Adjust turnbuckles on foot pedals.             |
| Machine turns in wrong direction per steering wheel. | Hydraulics plumbed incorrectly.        | Swap hoses to steering motor (refer to photo). |



Fig. 56 STEERING HOSES



## 8 SPECIFICATIONS

### 8.1 MECHANICAL

| <b>Description</b>          | <b>GR-400</b>                        |
|-----------------------------|--------------------------------------|
| Engine                      | 14 HP Kohler                         |
| Electric starter            | Standard                             |
| Working light               | Standard                             |
| Working width               | 40" (102 cm)                         |
| Height with trailer         | 66" (168 cm)                         |
| Width with trailer          | 52" (132 cm)                         |
| Length with trailer         | 97" (246 cm)                         |
| Machine weight              | 940 lbs (427.3 kg)                   |
| Shipping weight             | 1555 lbs (706 kg)                    |
| Shipping dimensions (L-W-H) | 55" X 53" X 72" (140 X 135 X 183 cm) |

**SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE**

## 8.2 HYDRAULIC FITTING TORQUE

### Tightening Flare Type Tube Fittings \*

1. Check flare and flare seat for defects that might cause leakage.
2. Align tube with fitting before tightening.
3. Lubricate connection and hand tighten swivel nut until snug.
4. To prevent twisting the tube(s), use two wrenches. Place one wrench on the connector body and with the second tighten the swivel nut to the torque shown.

| Tube Size OD<br>(in.) | Nut Size Across Flats<br>(in.) | Torque Value* |           | Recommended Turns To Tighten (After Finger Tightening) |            |
|-----------------------|--------------------------------|---------------|-----------|--|------------|
|                       |                                | (N.m)         | (lb-ft)   | (Flats)  | (Turn)     |
| 3/16                  | 7/16                           | 8             | 6         | 1  | 1/6        |
| 1/4                   | 9/16                           | 12            | 9         | 1  | 1/6        |
| 5/16                  | 5/8                            | 16            | 12        | 1  | 1/6        |
| <b>3/8</b>            | <b>11/16</b>                   | <b>24</b>     | <b>18</b> | <b>1</b>   | <b>1/6</b> |
| 1/2                   | 7/8                            | 46            | 34        | 1  | 1/6        |
| 5/8                   | 1                              | 62            | 46        | 1  | 1/6        |
| 3/4                   | 1-1/4                          | 102           | 75        | 3/4  | 1/8        |
| 7/8                   | 1-3/8                          | 122           | 90        | 3/4  | 1/8        |

- The torque values shown are based on lubricated connections as in reassembly.


## 8.3 BOLT TORQUE

### CHECKING BOLT TORQUE

The tables shown below give correct torque values for various bolts and capscrews. Tighten all bolts to the torques specified in chart unless otherwise noted. Check tightness of bolts periodically, using bolt torque chart as a guide. Replace hardware with the same strength bolt.


### ENGLISH TORQUE SPECIFICATIONS

| Bolt Diameter "A" | Bolt Torque * |         |       |         |       |         |
|-------------------|---------------|---------|-------|---------|-------|---------|
|                   | SAE 2         |         | SAE 5 |         | SAE 8 |         |
|                   | N.m           | (lb-ft) | N.m   | (lb-ft) | N.m   | (lb-ft) |
| 1/4"              | 8             | (6)     | 12    | (9)     | 17    | (12)    |
| 5/16"             | 13            | (10)    | 25    | (19)    | 36    | (27)    |
| 3/8"              | 27            | (20)    | 45    | (33)    | 63    | (45)    |
| 7/16"             | 41            | (30)    | 72    | (53)    | 100   | (75)    |
| 1/2"              | 61            | (45)    | 110   | (80)    | 155   | (115)   |
| 9/16"             | 95            | (70)    | 155   | (115)   | 220   | (165)   |
| 5/8"              | 128           | (95)    | 215   | (160)   | 305   | (220)   |
| 3/4"              | 225           | (165)   | 390   | (290)   | 540   | (400)   |
| 7/8"              | 230           | (170)   | 570   | (420)   | 880   | (650)   |
| 1"                | 345           | (225)   | 850   | (630)   | 1320  | (970)   |



### METRIC TORQUE SPECIFICATIONS

| Bolt Diameter "A" | Bolt Torque* |         |       |         |
|-------------------|--------------|---------|-------|---------|
|                   | 8.8          |         | 10.9  |         |
|                   | (N.m)        | (lb-ft) | (N.m) | (lb-ft) |
| M3                | .5           | .4      | 1.8   | 1.3     |
| M4                | 3            | 2.2     | 4.5   | 3.3     |
| M5                | 6            | 4       | 9     | 7       |
| M6                | 10           | 7       | 15    | 11      |
| M8                | 25           | 18      | 35    | 26      |
| M10               | 50           | 37      | 70    | 52      |
| M12               | 90           | 66      | 125   | 92      |
| M14               | 140          | 103     | 200   | 148     |
| M16               | 225          | 166     | 310   | 229     |
| M20               | 435          | 321     | 610   | 450     |
| M24               | 750          | 553     | 1050  | 774     |
| M30               | 1495         | 1103    | 2100  | 1550    |
| M36               | 2600         | 1917    | 3675  | 2710    |



Torque figures indicated above are valid for non-greased or non-oiled threads and heads unless otherwise specified. Therefore, do not grease or oil bolts or capscrews unless otherwise specified in this manual. When using locking elements, increase torque values by 5%.

\* Torque value for bolts and capscrews are identified by their head markings.







**AGRIMETAL INC.  
1006 PRINCIPALE  
WICKHAM, QUEBEC  
CANADA, J0C 1S0**

**TEL: (819) 398-6883  
FAX: (819) 398-5311**